

Intelligent Safety Analyzer



GPT-12000 Series

AC/DC/IR/GB Electrical Safety Analyzer

- 200VA AC Test Capacity
- 7" LCD Color Display
- Capacitive Load Testing Capability Up to 47 μ F
- Controllable Ramp Up & Ramp Down Time
- Statistics Function
- Testing Time Starting From 0.3s
- Provide USB Flash Drive Storage Function
- Universal Power Input

Function Model	Output Capacity	AC	DC	IR	GB	Continuity	Rear Output
GPT-12001	200VA	✓				✓	✓
GPT-12002	200VA	✓	✓			✓	✓
GPT-12003	200VA	✓	✓	✓		✓	✓
GPT-12004	200VA	✓	✓	✓	✓	✓	✓

NEW

7" LCD



www.gwinstek.com

GW INSTEK

Simply Reliable

SPECIFICATIONS

AC WITHSTANDING		
Output-Voltage Range	0.050kV~5.000kV	
Output-Voltage Resolution	1V	
Output-Voltage Accuracy	±(1% of setting + 5V) [no load]	
Maximum Rated Load	200 VA (5kV/40mA)	
Maximum Rated Current	40mA (0.5kV < V ≤ 5kV); 10mA (0.05kV ≤ V ≤ 0.5kV)	
Output-Voltage Waveform	Sine wave	
Output-Voltage Frequency	50 Hz / 60 Hz selectable	
Voltage Regulation	±(1% + 5V) [maximum rated load -- no load]	
Voltmeter Accuracy	±(1% of reading + 5V)	
Current Measurement Range	1μA~40.00mA	
Current Best Resolution	1μA / 10μA	
Current Measurement Accuracy	±(1.5% of reading + 30μA)	
Window Comparator Method	Yes	
ARC Detect	Yes	
RAMP UP (Rise Time)	0.1s~999.9s	
RAMP DOWN (Fall Time)	0.0s~999.9s	
TIMER (Test Time)	OFF, 0.3s~999.9s	
WAIT TIME	0.0s~999.9s	
GND	ON/OFF	
DC WITHSTANDING		
Output-Voltage Range	0.050kV~6.000kV	
Output-Voltage Resolution	1V	
Output-Voltage Accuracy	±(1% of setting + 5V) [no load]	
Maximum Rated Load	50W (5kV/10mA)	
Maximum Rated Current	10mA (0.5kV < V ≤ 6kV); 2mA (0.05kV ≤ V ≤ 0.5kV)	
Voltage Regulation	±(1% + 5V) [maximum rated load -- no load]	
Voltmeter Accuracy	±(1% of reading + 5V)	
Current Measurement Range	1μA~10.00mA	
Current Best Resolution	0.1μA / 1μA / 10μA	
Current Measurement Accuracy	±(1.5% of reading + 3μA) when I Reading < 1mA; ±(1.5% of reading + 30μA) when I Reading ≥ 1mA	
Window Comparator Method	Yes	
ARC Detect	Yes	
RAMP UP (Rise Time)	0.1s~999.9s	
RAMP DOWN (Fall Time)	0.0s~999.9s	
TIMER (Test Time)	OFF, 0.3s~999.9s	
WAIT TIME	0.0s~999.9s	
GND	ON/OFF	
INSULATION RESISTANCE		
Output Voltage	50V~1200V dc	
Output-Voltage Resolution	50V	
Output-Voltage Accuracy	±(1% of setting + 5V) [no load]	
Resistance Measurement	Measurement Range / Accuracy	
Test Voltage	Display Range	
50V ≤ V ≤ 100V	0.1M Ω ~ 10.00G Ω	0.1MΩ~1MΩ : ±(5% of reading + 3 count); 1 MΩ~50MΩ : ±(5% of reading + 1 count);
150V ≤ V ≤ 450V	0.1M Ω ~ 20.00G Ω	51MΩ~2GΩ : ±(10% of reading + 1 count)
500V ≤ V ≤ 1200V	0.1M Ω ~ 50.00G Ω	0.1MΩ~1MΩ : ±(5% of reading + 3 count); 1 MΩ~500MΩ : ±(5% of reading + 1 count);
		501MΩ~9.999GΩ : ±(10% of reading + 1 count); 10GΩ~50GΩ : ±(20% of reading + 1 count)
Voltage Regulation	±(1% + 5V) [maximum rated load -- no load]	
Voltmeter Accuracy	±(1% of reading + 5V)	
Short-Circuit Current	10mA max.	
Output Impedance	2kΩ	
Window Comparator Method	Yes	
RAMP UP (Rise Time)	0.1s~999.9s	
RAMP DOWN (Fall Time)	0.0s~999.9s	
TIMER (Test Time)	0.3s~999.9s	
WAIT TIME	0.0s~999.9s	
GND	ON/OFF	
GROUND BOND		
Output-Current	03.00A~32.00A ac	
Output-Current Resolution	0.01A	
Output-Current Accuracy	3A ≤ I ≤ 8A : ±(1% of reading + 0.2A); 8A < I ≤ 32A : ±(1% of reading + 0.05A)	
Test-Voltage	8Vac max (open circuit)	
Test-Voltage Frequency	50Hz/60Hz selectable	
Ohmmeter Measurement Range	1mΩ~ 650mΩ	
Ohmmeter Measurement Resolution	0.1mΩ	
Ohmmeter Measurement Accuracy	±(1% of reading + 2 mΩ)	
Window Comparator Method	Yes	
TIMER (Test Time)	0.3s~999.9s	
Test Method	Four Terminal	
GND	ON/OFF	
CONTINUITY TEST		
Output-Current	100mA dc (fixed)	
Ohmmeter Measurement Range	0.10Ω~ 90.00Ω	
Ohmmeter Measurement Resolution	0.01Ω	
Ohmmeter Measurement Accuracy	±(10% of reading + 2 Ω)	
MEMORY		
Single Step Memory	MANU : 100 blocks	
Automatic Testing Memory	AUTO : 100 blocks, Manu per auto : 10	
INTERFACE		
Standard (Front)	REMOTE, USB host	
Standard (Rear)	Rear Output, RS-232C, USB device, Signal I/O,	
Option	GPIB	
DISPLAY		
	7" color LCD	
POWER SOURCE		
	AC 100V~240V ± 10%, 50Hz/60Hz; Power consumption : Max. 400VA	
DIMENSIONS & WEIGHT		
	380(W) x 148(H) x 454(D) mm; Approx. 15kg	

Specifications subject to change without notice. GPT-12000CD1DH

ORDERING INFORMATION

GPT-12004	AC/DC/IR/GB Electrical Safety Analyzer
GPT-12003	AC/DC/IR Electrical Safety Analyzer
GPT-12002	AC/DC Electrical Safety Analyzer
GPT-12001	AC Electrical Safety Analyzer

ACCESSORIES

Quick Start Guide x 1, Power cord x 1, CDx1 (complete user manual), Interlock Key x 1, Remote terminal Cable GHT-119 x 1, Test lead GHT-115 x 1 for GPT-12001/12002/12003, Test lead GHT-115 x 1, GTL-215 x 1 for GPT-12004

OPTION

Opt.1 GPIB card

OPTIONAL ASSESSORIES

GHT-113	High Voltage Test Pistol	GHT-118	HV/GB Adapter
GHT-117	HV Adapter	GHT-205	High Voltage Test Probe
GTL-248	GPIB Cable, approx. 2m		
GTL-247	USB Cable, A-A type, approx. 1.8m		
GTL-232	RS-232C Cable, 9-pin Female to 9-pin null Modem for Computer		

GOOD WILL INSTRUMENT CO., LTD.

No.7-1, Jhongsing Road, Tucheng Dist., New Taipei City 236, Taiwan
 T +886-2-2268-0389 F +886-2-2268-0639
 E-mail: marketing@goodwill.com.tw



www.gwinstek.com www.facebook.com/GWInstek

GW INSTEK
Simply Reliable